

Stage Lighting








Applications

- **Concert**
- **Moving Heads**
- **Strobes**
- **Architainment**
- **Show Studio**
- **Theater / Stage**
- **Church / School**
- **etc.**



Stage Lighting - LED Portfolio

[Click here to link to main website Product Catalog](#)

Part	Colors Available	Wavelength / Coordinates	Intensity Range (@ bin current)	Current - mA Bin / Max	Viewing Angle	Size - mm (L x W x H)	Product Selector Guide by Application ✓ - recommendation		
							Moving Heads	Strobes	Architainment
OSRAM OSTAR® Stage (multi-color)									
 LE RTDCY S2WN	R / T / D / CY	625 / 525 / 453 nm / 0.57, 0.42	90-140 lm / 140-280 lm / 1120-1800 mW / 140-280 lm	1000 / 2500	120° 130° (CY)	4.68 x 5.75 x 1.26	✓		✓
 LE RTDUW S2WN	R / T / D / UW	625 / 525 / 453 nm / 0.31, 0.32	90-140 lm / 140-280 lm / 970-1500 mW / 180-355 lm	1000 / 2500	120° 130° (UW)	4.68 x 5.75 x 1.26	✓		✓
 LE RTDUW S2WP	R / T / D / UW	625 / 530 / 453 nm / 0.32, 0.33	90-224 lm / 224-450 lm / 1120-2240 mW / 280-560 lm	1400 / 4500	120° 130° (UW)	5.75 x 6.38 x 1.26	✓		✓
LE RTDUW S2W	R / T / D / UW	625 / 527 / 453 nm / 0.31, 0.32	45-112 lm / 90-180 lm / 630-900mW / 140-224 lm	700 / 1000	120°	4.68 x 5.75 x 1.1	✓		✓
OSRAM OSTAR® Projection Compact (single-color)									
 KW CSLNM1.TG KW CSLPM1.TG KP CSLNM1.F1 KP CSLPM1.F1 KB CSLNM1.14 KR CSLNM1.23	W W P P B R	0.32, 0.33 0.32, 0.33 0.32, 0.64 0.32, 0.64 455 nm 617 nm	250 - 400 lm 355 - 560 lm 280 - 500lm 450 - 710 lm 900 - 1590 mW 100 - 180 lm	1000 / 3000 1400 / 5000 1000 / 3000 1000 / 3000 1400 / 5000 1000 / 3000	120°	3.0 x 3.0 x 0.75	✓	✓	✓
 LE x Q7WP	B / A CG	459 / 617 / 0.32, 0.64	2800-4500 mW / 280-520 / 900-1400 lm	1400 / 5000	120° 130° (CG)	4.68 x 5.75 x 1.25	✓	✓	✓
 LE x Q8WP	B / T / A / R / CG / UW	459 / 530 / 617 / 625 nm / 0.32, 0.64 / 0.32, 0.33	1400-2240 mW / 224-450 / 130-210 / 90-224 / 450-710 / 280-560 lm	1400 / 5000 1400 / 3500 (A)	120° 130° (CG & UW)	3.65 x 3.9 x 1.22	✓	✓	✓
OSLON® Signal (single-color)									
 LB CRBP LCB CRBP Lx CQBP Lx CKBP LCY CLBP LUW CRBP	B CB V / T Y / J CY UW	475 nm 0.16, 0.12 505 / 528 nm 590 / 617-632 nm 0.57, 0.42 0.34, 0.33	28-52 lm 45-82 lm 61-130 / 82-130 lm 33-82 / 45-112 lm 71-112 lm 112-180 lm	350 / 1000	120° 125° 130° 125° 125° 120°	3.0 x 3.0 x 1.7	✓	✓	✓

x = colors available

Color Legend: A=Amber, B=Blue, CB=Converted Blue, CG=Converted Green, CY=Converted Yellow, D=Deep Blue, J=Red, P=Pure Green, R=Red, T=True Green, UW=Ultra White, V=Verde Green, W=White, Y=Yellow

Light is OSRAM

Status 07-2017 - OSRAM Opto Semiconductors - Suggested Parts - Check website for all product offerings & datasheets
Images not to scale - Subject to change without notice - Errors and omission excepted

OSRAM
Opto Semiconductors