

Power Products

Product Name	Circuit Size	Current (Max) Per Pin	Versions	PCB Termination	Pitch	Available Configurations Wire Gauge (AWG)
KK [®] 254	2 to 24	4.0A	Single Row Through Hole	2.54mm (0.100")	W-to-B, B-to-B	22 to 28
Micro-Fit 3.0 [™]	2 to 24	5.0A	Dual Row Through Hole and Compliant Pin	3.0mm (0.118")	W-to-W, W-to-B	20 to 30
Micro-Fit BMI [™] (Blind Mate Interface)	4 to 24	5.0A	Single & Dual Row Through Hole and Compliant Pin	3.0mm (0.118")	W-to-B, B-to-B	18 to 24
KK [®] 396	2 to 24	7.0A	Single Row Through Hole	4.20mm (0.165")	W-to-W, W-to-B	16 to 24
Mini-Fit Jr. [™]	2 to 24	13.0A	Single & Dual Row Through Hole	4.20mm (0.165")	W-to-W, W-to-B, B-to-B	16 to 24
Mini-Fit BMI [®] (Blind Mate Interface)	2 to 24	13.0A	Single & Dual Row Through Hole and Compliant Pin	4.20mm (0.165")	W-to-W, W-to-B, B-to-B	16 to 24
Ultra-Fit [™]	2 to 8 (Single Row), 4 to 16 (Dual Row)	14.0A	Single & Dual Row Through Hole	3.50mm (0.138")	W-to-B	16 to 22
Sabre [™]	2 to 8	18.0A	Single Row Through Hole	7.50mm (0.295")	W-to-W, W-to-B	14 to 18
Mega-Fit [®]	2 to 12	23.0A	Single Row Through Hole	5.70mm (0.224")	W-to-B	12 to 16
Super Sabre [™]	2 to 8	34.0A	Single Row Through Hole	7.50mm (0.295")	W-to-W, W-to-B	10 to 12